

PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER OF PATENTS AND TRADEMARKS P.O. DOX 1450 Alexandria, Vigonia 22313-1450 www.uspbu.gov

FILING OR 371 APPL NO. **ART UNIT** FIL FEE REC'D TOT CLMS ATTY.DOCKET NO DRAWINGS IND CLMS (c) DATE 10/602,484 06/24/2003 2812 894 2000.106000 28 DEK KELLED!

J. Mike Amerson Williams, Morgan & Amerson, P.C. **Suite 1100** 10333 Richmond Houston, TX 77042

A: Required Publishinio . April "Litury Info.

CONFIRMATION NO. 1113

FILING RECEIPT

OC000000010846733

Date Mailed: 09/09/2003

Receipt is acknowledged of this regular Patent Application. It will be considered in its order and you will be notified as to the results of the examination. Be sure to provide the U.S. APPLICATION NUMBER, FILING DATE. NAME OF APPLICANT, and TITLE OF INVENTION when inquiring about this application. Fees transmitted by check or draft are subject to collection. Please verify the accuracy of the data presented on this receipt. If an error is noted on this Filing Receipt, please write to the Office of Initial Patent Examination's Filing Receipt Corrections, facsimile number 703-746-9195. Please provide a copy of this Filing Receipt with the changes noted thereon. If you received a "Notice to File Missing Parts" for this application, please submit any corrections to this Filing Receipt with your reply to the Notice. When the USPTO processes the reply to the Notice, the USPTO will generate another Filing Receipt incorporating the requested corrections (if appropriate). DOCKETING DEPT.

Applicant(s)

Michael Friedemann, Dresden, GERMANY: Volker Kahlert, Dresden, GERMANY:

SEP 1 2 2003

WILLIAMS, MORGAN & AMERSON

Domestic Priority data as claimed by applicant

Foreign Applications

GERMANY 102 61 466.0 12/31/2002

If Required, Foreign Filing License Granted: 09/08/2003

Projected Publication Date: 07/01/2004

Non-Publication Request: No

Early Publication Request: No

Title

Method of forming a conductive barrier layer having improve adhesion and resistivity characteristics